

Y	Yellow	黄色
W	White	白色
U	Blue	蓝色
R	Red	红色
O	Orange	橙色
G	Green	绿色
B	Black	黑色
A	Gray	灰色
CAP COLOR (X)		

Specifications

Circuit	:SPST
Current rating	:30mA
Voltage rating	:30VDC
Dielectric withstanding voltage	:500VAC for 1 minute
Contact resistance	:30m Ω Max. (Initial)
Insulation resistance	:100M Ω Min
Operating force	:300±50gf
Total travel	:0.7mm±0.2mm
Operating life	:100,000 cycles Min.
Solder specifications	:260±5° C for 5 seconds
Operating temperature	:-20° C ~ +60° C
Welding method	:Manual Soldering (350° C±5° C, 3s±0.5s)

MATERIAL:

Frame:Nylon66,UL rated:94V-2 Min. ;

Cap:ABS;

Terminal: Brass, Gold or Tin plated.

				公差 TOLERANCES		.X± 0.3 .XX± 0.15		角度 ANGLE ± 1°		单位	DIMENSION UNIT mm.	
A2	重新整理	2016.12.12	N/A	视 角		比例尺	1:1	日 期	2016.12.12	品 名 TITLE		图 号
A1	重新整理	2016.07.02	N/A	VIEWING ANGLE		SCALE		DATE		TACT SWITCH		DRAWING NO
A0	发行	2011.12.01	N/A	核 准		核 对	Sinc	绘 图	P.W.RAO			XB-TS-1201
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY	Richard	CHECKED BY		DRAWN BY				