

RoHS
Compliant

SYMBOL	REVISION	APPROVAL	DATE

NOTE:
Material
Insulator: LCP
Contact: C2680
Contact Plated: Gold over Nickel or Tin
Specification
Current rating: 3A
instant CURRENT: 5A
Contact Resistance: 30mΩ
Insulation Resistance: 100MΩ
Dielectric Voltage: 500V
Operdting Temperature: -40°~105°

RECOMMENDED P.C.B LAYOUT
TOP VIEW (.XX±0.05)

2	HOUSING	LCP	1	GRAY
1	CONTACT TERMINAL	C2680	6	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING
PART NAME		DRAWING	Y.C.Zhang	DWG.No.
PART NO.		CHECK	G.C.Chen	REV.
	UNIT:	TOLERANCE	UP TO 5 ABOVE 5 ~30 ABOVE 30 ANGLE	ANGLE
	mm	OTHERWISE	±0.2 ±0.3 ±0.5 ±3°	0°±3°
			APPROVAL	SCALE
			2:1	
			DATE	01-05-2020
			PAGE	1 OF 1



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

COPYRIGHT RESERVED,PLEASE DO NOT COPY.