




产品规格书 Product Details specification

产品名称 Title	File No.	Version	Date	Page
XB-SW-3030-30光电开关	XB-SW-3D-027	2023-A3	2023.1.25	4/4




SIZE

Unit: mm,
Tolerance ± 0.25



水平板安装



注意事项 Note

1.If the product used for high security products and durability of extremely high equipment (such as life safety equipment, aviation facilities, disaster prevention device), please confirm whether a share, can seek advice our company for details.

如果该产品要用于高安全性产品及耐久性极高的设备中（如生命安全设备、航空设施、防灾装置），请确认是否合用，或咨询我司了解详情。

2.In case of fire, Please do not overload applicable.

请勿超负荷使用，以防发生火灾。

3.The welding temperature or time more than standard, can cause switch collapse.

焊接温度或时间超过规范时，会造成开关解体。

4.Do not use water solubility flux. May cause damage to the switch.

勿使用水溶性助焊剂、可能会造成开关损坏。

5.Do not use solvent wash switch.

勿使用溶剂清洗开关。

6.Xibang company is only responsible for the defective problems of the product itself, return and exchange the defective products, and does not bear other joint and several expenses.

溪榜公司只承担本产品本身不良问题,对不良品进行退换货,不承担其它连带费用责任。