




[illegible]

Base:PBT, UL rated: 94V-2 Min.;
Cap: ABS;
Terminal: Phosphor bronze, Golden plated.

Circuit	:SPDT
Current rating	:12mA
Voltage rating	:24VDC
Dielectric withstanding voltage	:250VAC for 1 minute
Contact resistance	:50m Ω Max. (Initial)
Insulation resistance	:100M Ω Min.
Operating force	:170 $\pm$ 50gf
Total travel	:2.0mm $\pm$ 0.4mm
Mechanical life	:Over 50,000 cycles
Electrical life	:Over 10,000 cycles
Solder specifications	:256 $\pm$ 5°C for 5 $\pm$ 0.5 seconds
Function	:Momentary
Operating temperature	:-20° C ~ +70° C



P.C.B . Layout



Circuit Diagram

				公差 TOLERANCES		.X± 0.3 .XX± 0.15		角度 ANGLE ± 1°		单位	DIMENSION UNIT mm.	
				视角		比例尺	NONE	日期	2015.10.07	品 名 TITLE		图 号
A1	电路图变更	2015.10.07	N/A	VIEWING ANGLE		SCALE		DATE				DRAWING NO
A0	New Issue	2010.10.04	N/A									
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核 准	Richard	核 对	Sinc	绘 图	Mashaofei			
				APPROVED BY		CHECKED BY		DRAWN BY				