

Circuit Diagram

SCHEMATIC

NO.1

PART NO	vigor
3	180±30
4	250±30

NO.2-NO.3

PART NO	NOTE
01~99	SERIAL NUMBER

Typical Specifications

1.Rating : DC 12V 50mA

2.Contact Resistance: ≤100mΩ

3.Lnsulation Resistance: ≥100MΩ DC250V

4.Operating Temperature Range:
-25℃+80℃

5.Ambient Humidity Used: ≤85%RH

6.Travel: 0.25±0.1mm

7.Life : 100,000 Cycles

8.IP Rating: IP65

8					TOLERANCE				
7					UNLESS SPECIFIED				
6					WITHIN 1.5mm : ±0.1mm	A	2012-9-25	初 版	ZENQ. CHEN
5					OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	CONTACT	SUS	1	Ag CLAD	TITLE : TACT SWITCH			UNIT : mm	DRWG NO.: XB-TS-1107SP
3	CASE	PPA/BRASS SRTIP	1	BLACK/Ag PLATED	MODEL:			SCALE: 5:1	DWN. JUN. YANG 2012-9-25
2	COVER	STEEL STRIP	1	Ni PLATED	东莞市溪榜电子有限公司			CHK'D	DONG. PANG 2012-9-25
1	KNOB	PPA	1	BLACK				APPD.	ZENQ. CHEN 2012-9-25
NO.	PARTS	MATERIALS	Q'TY	FINISH	Switch Connector DONG GUAN XI BANG ELECTRONI CS CO., LTD.				