

## XB Product features

Voltage: < 12V

Current: < 20mA

Conduction time: 2ms

Closed circuit resistance: < 10m ohm

Open circuit resistance: > 10m ohm

High temperature resistance: 120degrees

Terminal tension: 500gf / min

Humidity: 25~95%RH

Operating life: 100000 times

## XB Product features XB产品特性

1.SW-168 is double ball type single direction tilt induction trigger switch.

1.SW-168为双球型单向倾斜感应触发开关。

2. When the electric end of the product guide (foot less) is tilted and the tilt Angle is greater than 10 degrees, the product is in the open, (OFF) state. When the horizontal state of the product is tilted and the trigger end (gold-plated pin end) is lower than the horizontal and the tilt Angle is greater than 10 degrees, the product is in the closed, (ON) state.

2.当产品导轨（无脚）的电气端倾斜且倾斜角度大于10度时，产品处于打开（关闭）状态。当产品水平状态倾斜，触发端（镀金销端）低于水平且倾斜角度大于10度时，产品处于闭合（开）状态。

3. When placed horizontally, shaking can be easily triggered, and when there is no foot down, shaking is not easy to trigger.

3.水平放置时，很容易触发震动，没有脚下来时，不容易触发震动。

4. The products of this specification are completely sealed, waterproof and dustproof.


4.本规范产品全密封、防水、防尘。

5. Under normal circumstances, the switching life can reach 100,000 times.

5.正常情况下，开关寿命可达10万次。

6. This product is made of environment-friendly metal material with stable performance. XB

6、本产品采用环保型金属材料，性能稳定。



⑥	Plug	1	PC		
⑤	Ball	1	Brass	SC	_____
④	Ball	1	Brass	SC&GP2U	_____
③	Pin A	1	Brass	SILVERING	_____
②	Pin B	1	Brass	GP 2U	_____
①	Copper Pipe	1	Brass	SC&GP2U	_____
ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING	REMARK

				ANGLAR	±5°
				L≤ 4	±0.2
				4<L≤ 16	±0.3
				16<L≤ 63	±0.4
	DATE	REVISED	APPROVED	L> 63	±0.5
					UNSPECIFIED TOLERANCES
www.alpsr.com www.gdxjdz.com www.xbswitch.com					



DSND		SCALE: N/A	MODEL TYPE: Vibration switch		
DWN		VIEW:	PART NO.:		
CHKD		UNIT: mm/in	DWG NO.:		
APPD		SIZE: A4			
DONG GUAN XI BANG ELECTRONIC CO., LTD			WEIGHT	SHEET 1/1	REVISIC A0