






CAD FILE:

ROHS



CIRCUIT DESCRIPTION



- 额定值 RATING: 8A 125/250VAC(UL, C-UL)
12A-8(3)A 250V~ μT125/55 (ENEC-17, CQC, CB)
- 功能 FUNCTIONAL: 见电路图 SEE CIRCUIT DESCRIPTION
带回弹功能 PLUS A MOMENTARY POSITION
- 接触电阻 CONTACT RESISTANCE: <50mΩ
- 绝缘电阻 INSULATION RESISTANCE: >100MΩ (500VDC BETWEEN OPEN CONTACTS)
- 耐电压 DIELECTRIC STRENGTH: >1500VAC 0.5mA 1 MINUTE
- "○"表示关键尺寸 DENOTES CRITICAL DIMENSIONS

8					TOLERANCE				
7					UNLESS SPECIFIED				
6					WITHIN 1.5mm : ±0.1mm	A	2012-9-25	初版	ZENQ. CHEN
5					OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	CONTACT	SUS	1	Ag CLAD	TITLE : 电源旋转开关			UNIT : mm	DRWG NO.: XB-MFR01-A5M02L14BS-R
3	CASE	PPA/BRASS SRTIP	1	BLACK/Ag PLATED	MODEL: Power Rotary Switch			SCALE: 5:1	DWN. JUN. YANG 2012-9-25
2	COVER	STEEL STRIP	1	Ni PLATED	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.			CHK'D DONG. PANG 2012-9-25	
1	KNOB	PPA	1	BLACK				APPD. ZENQ. CHEN 2012-9-25	
NO.	PARTS	MATERIALS	Q'TY	FINISH					