




REV.	DESCRIPTION	DRAW.	DATE.
01	NEW DESIGN	Elih	2016.05.05

No. of Pins	Dimension	
	DIM.B	DIM.A
02	2.00	6.50
03	4.00	8.50
04	6.00	10.50
05	8.00	12.50
06	10.00	14.50
07	12.00	16.50
08	14.00	18.50
09	16.00	20.50
10	18.00	22.50
11	20.00	24.50
12	22.00	26.50
13	24.00	28.50
14	26.00	30.50
15	28.00	32.50
16	30.00	34.50

Material
Insulator:Nylon 9T(UL94V-0)
TERMINAL: C2680
TERMINAL:Plated Gold over
Nickel or Tin
Specification
Current rating:8A
instant CURRENT:12A
Contact Resistance:30mΩ
Insulation Resistance:100MΩ
Dielectric Voltage:500V
Operdting
Temperature:-40°~105°

XGB 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONI CS CO., LTD.

UNLESS OTHERWISE SPECIFIED,TOLERANCE: X. ±0.50 X.x ±0.30 X.xx ±0.20 ANGULAR ±2°	DESIGN		DATE		TITLE:	
	APPROVED		DATE			
	PART	XB-C01M-W-2P-R4		REV: 01	SCALE:1:1	UNIT: mm
	DRAWING	XB-C01M-W-2P-16P		SIZE: A4	SHEET:1/1	