



OJ-0001A-xx x xx-S141

Housing Color :

Black: Blank
Green: GR
Red: R

端子鍍層:

Ag: Blank
Au: G

No Special Option : 00

Transmit Signal by Fiber : T0

Receive Signal by Fiber : R0

SPECIFICATION

1. Rating : DC 30V 0.5A
2. Contact resistance : $\leq 30m\Omega$
3. Insulation resistance : $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

10	Fiber	1		
9	Shell	6	Brass	Nickel Plating
8	Make terminal	5	Phosphor bronze	
7	Transfer terminal	4	Phosphor bronze	
6	Ring spring	3	Phosphor bronze	
5	Tip spring	2	Phosphor bronze	
4	Earth spring	1	Phosphor bronze	
3	Cover	1	PA9T	
2	Housing(B)	1	PA9T	
1	Housing(A)	1	PA9T	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

XB 东莞市溪榜电子有限公司
Switch Connector DONG GUAN XI BANG ELECTRONICS CO., LTD.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
06/22/18
DATE
06/22/18
DATE
06/22/18

MAT'L
FINISH
SCALE

1 : 1

TITLE
MODLE
DWG NO.

JACK
OPTICAL JACK

OJ-0001A-xx x xx-S141

PART NO. OJ-0001A-xx x xx-S141

SIZE
A4
VER
R

1	更新料號	Jack	062218
ITEM NO.	DESCRIPTION	DRAWN	DATE