

电流电路
CURRENT CIRCUIT

位置POSITION	电路CIRCUIT
1(INITIAL)起始	OFF
2	C+1

C —  — **1**


- 1.滑动开关型号 SLIDE SWITCH MODEL: KND-1-DH002-R2
- 2.焊线端子 SOLDER CONNECTOR TYPE:
单刀单掷 SINGLE POLE SINGLE THROW
- 3.额定值 RATING: 16(4)A 125/250VAC μ T105 (CQC;ENEC17;NEMKO;UL,KC)
10(2)A 125/250VAC μ T105 (UL)
7(2)A 125/250VAC μ T105 (UL)
10(2)A 125/250VAC μ T85 (CQC;ENEC17;NEMKO)
7(2)A 125/250VAC μ T85 (CQC;ENEC17;NEMKO)
- 4.接触电阻 CONTACT RESISTANCE: <50m Ω (INITIAL)
- 5.绝缘电阻 INSULATION RESISTANCE: $\geq$ 100M Ω (DC500V/1MIN)
- 6.介电强度 DIELECTRIC STRENGTH: 1500V /5mA /1MIN
- 7.机械寿命 MECHANICAL LIFE: >50000 CYCLES
- 8.电气寿命 ELECTRICAL LIFE: >10000 CYCLES
- 9.端子手工焊接条件 SOLDER ABILITY OF TERMINAL: MAX260°C, 3S
- 10.操作力 OPERATION FORCE:55 $\pm$ 150gf
- 11.所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT

The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.



TITLE : XB SLIDE SWITCH

MODEL : XB-KND-1-DH002-R2 大电流2档开关16A 电吹风两档开关10A



TOLERANCE
 $\leq 1.5\text{mm} \pm 0.1$
 $> 1.5\text{mm} \pm 0.2$
 $\geq 10\text{mm} \pm 0.3$

ANGLE
 $\pm 2^\circ$

7	SPRING	STEEL WIRE	1	NATURE
6	STEEL BALL	STEEL	1	NATURE
5	BOARD	PHENOLIC RESIN	1	NATURE
4	CONTACT CLIP	PBS STRIP	2	Ag PLATED
3	FRAME	IRON STRIP	1	Ni PLATED
2	TERMINAL	BRASS STRIP	8	Ag PLATED
1	KNOB	POM	1	BLACK
NO.	PART NAME	MATERIAL	QTY.	FINISHING