



NOTE:
 1. ELECTRICAL CHARACTERISTICS
 1-1. CONTACT RESISTANCE
 80 milliohms MAX.
 1-2. INSULATION RESISTANCE:
 1,000 Megohms MIN
 1-3. DIELECTRIC WITHSTANDING
 VOLTAGE: 500V AC FOR 1 MINUTE
 2. MECHANICAL CHARACTERISTICS
 RETENTION FORCE: MIN. 100gf/PIN
 3. RoHS 2002/95/ECCOMPLIANT

RECOMMENED P.C.B LAYOUT(TOP VIEW)
 GENERAL TOLERANCE ±0.05

ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING
③	PEG	1	COPPER ALLOY	
②	Terminal	8	COPPER ALLOY	
①	Housing	1	HI-TEMP.PLASIC UL 94V-0	BLACK

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
				ANGLAR ±5°
				L ≤ 4 ±0.2
				4 < L ≤ 16 ±0.3
				16 < L ≤ 63 ±0.4
				L > 63 ±0.5

www.alpsr.com www.gdxjdz.com www.xbswitch.com



DSND	SCALE: N/A	MODEL TYPE: TF CARD CONN
DWN	VIEW:	PART NO.: XKTF-004
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	
DONG GUAN XI BANG ELECTRONIC CO., LTD		WEIGHT SHEET REVISION 1/1 A0